

1911 GRIP BUSHING EXTRACTOR - CHALLIS GRIPS 1911 GRIP BUSHING EXTRACTOR, SLIM

[Gunsmith Tools](#) > [Handgun Tools](#) > [Grip Tools](#)

Easy & Effective Bushing Removal

Challis bushing extractors are attached to the bushing with a standard grip screw. With the bushing held captive, the drive teeth cannot slip out of engagement and the top of the bushing will not peel off. Significant torque can be applied with the included lever.



Attributes

- Name: [CHALLIS GRIPS 1911 GRIP BUSHING EXTRACTOR, SLIM](#)
- Manufacturer: [CHALLIS GRIPS](#)
- Product no.: 100017842
- Mfr. No.: T-SBE
- Weapon type: 1911
- Delivery weight: 0.032kg
- Shipping height: 25mm
- Shipping width: 64mm
- Shipping length: 152mm
- UPC: 080687718993

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [1911 Grip Bushing Extractor Safety Instructions](#)
- [About Us](#)

1911 Grip Bushing Extractor Safety Instructions

Introduction

Thank you for choosing the 1911 Grip Bushing Extractor by Challis Grips. This tool is designed to provide safe and efficient removal of standard size or slim 1911 grip bushings. Please read this safety instruction guide carefully to ensure safe usage and compliance with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Ensure the product is used only for its intended purpose.
- Always inspect the tool before use for any signs of damage or wear.
- Keep the tool out of reach of children and vulnerable individuals.
- Report any unsafe products or incidents to the appropriate authorities.
- Stay informed about product recalls through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Always wear appropriate personal protective equipment (PPE), such as safety glasses and gloves, when using the extractor.
- Ensure the grip bushing extractor is securely attached to the bushing before applying torque.
- Do not exceed the recommended torque when using the lever to avoid damage to the bushing or the extractor.
- Avoid using the extractor in wet or damp conditions to prevent slipping and potential injury.
- Do not use the extractor if it is damaged or if the grip screw is not functioning correctly.

Instructions for Installation and Usage

1. Preparation:

- Ensure that the workspace is clean and welllit.
- Gather all necessary tools and equipment.

2. Attaching the Extractor:

- Align the extractor with the grip bushing.
- Insert the standard grip screw through the extractor and into the bushing.
- Tighten the grip screw securely to hold the bushing captive.

3. Using the Extractor:

- Once the bushing is secured, use the lever included with the extractor to apply torque.
- Gradually increase torque until the bushing begins to loosen. Do not apply excessive force.
- If the bushing does not loosen, check for proper attachment and ensure no obstructions are present.

4. Removing the Extractor:

- Once the bushing is removed, carefully unscrew the grip screw to detach the extractor.
- Store the extractor in a safe place to prevent damage.

Disposal Instructions

- Dispose of the product in accordance with local regulations.

- Do not dispose of the product in household waste.
- Consider recycling options if applicable.

Contact Information for Further Support

For any inquiries or support regarding the 1911 Grip Bushing Extractor, please refer to the manufacturer's contact information provided on the packaging or product documentation.

Thank you for choosing the 1911 Grip Bushing Extractor. Your safety is our priority.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk