

XRT X-RINGS PICATINNY SCOPE RINGS - TPS PRODUCTS XRT ALUMINUM RINGS 30MM LOW

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

XRT Series X-Rings, bringing a whole new level of beauty and precision into an extremely rugged Picatinny platform scope mount. The X-Rings have been built from the bottom up to provide the extreme precision and accuracy that TPS rings have been known for over the last two decades. The ring bases begin from a solid billet of 7075-T6 aluminum and then machined with our unique Double-Lug Picatinny recoil shoulders from the solid billet. We have designed and engineered the Double-Lug recoil system to allow the parallelism and perpendicularity of the lugs to the ring bore to be within .0002, thereby providing repeatability that no other mount in the world with similar integrated lugs has done before. The X-Rings are specifically designed for the Mil-STD 1913 rail system. Because of the Double-Lug system, they do require two (2) accompanied cross-slots in a 1913 cross-slot configuration. The ring caps are secured with Four (4) 8-32 x 1/2" Camcar-Textron Torx drive screws and with the same unique design that allows you to tighten the left side of the cap, then the right side without the scope rotating. The edges and corners are fully radiused, preventing snagging, and providing a beautiful appearance to your rifle. The rings are securely attached to your rail with an oversized clamp system using Two (2) 8-32 x 1/2" Camcar-Textron Torx screws, preventing any chance your rings will loosen or move once installed. With unparalleled precision and holding force, and sleek design, these will meet the extreme expectations of any class shooter. SPECS: 7075-T651 Aluminum Alloy, matte black, hard anodized to Mil-A-8625 standards. .700" (17.8mm) wide. Height measured from the top of base to center of the ring. 30mm - High: .1.075" (31.11mm).



Attributes

- Name: [TPS PRODUCTS XRT ALUMINUM RINGS 30MM LOW](#)
- Manufacturer: [TPS PRODUCTS](#)
- Product no.: 100036961
- Mfr. No.: 50580
- Finish: Matte Blue
- Height: .925"
- Material: Aluminum
- Scope Tube Diameter: 30mm
- Size: Low
- Style: Tactical Rings
- Delivery weight: 0.181kg
- Shipping height: 64mm
- Shipping width: 64mm
- Shipping length: 127mm
- UPC: 071611505802

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for XRT XRINGS Picatinny Scope Rings](#)
- [About Us](#)

Safety Instruction Guide for XRT XRINGS Picatinny Scope Rings

Introduction

Thank you for choosing the XRT XRINGS Picatinny Scope Rings by TPS Products. This guide provides essential safety instructions and guidelines to ensure the safe use and installation of your scope rings. Adhering to these guidelines will help you avoid potential hazards and ensure optimal performance.

General Safety Guidelines

- Ensure that the product is suitable for your specific firearm and scope before installation.
- Always check for any visible damage or defects before use. Do not use if damaged.
- Keep the product out of reach of children and vulnerable individuals.
- Use the product only for its intended purpose as specified in the product description.
- Report any unsafe product conditions or incidents to the appropriate authorities.
- Stay informed about product recalls by checking the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Verify that the scope rings are compatible with your Picatinny rail system.
- Ensure that all screws are tightened securely before use to prevent loosening during operation.
- Avoid overtightening screws, as this may damage the scope or rings.
- Regularly inspect the scope rings for wear or loosening, especially after extensive use.
- Do not modify or alter the scope rings in any way.
- Always use protective eyewear when handling firearms and related accessories.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a Torx drive screwdriver.
- Ensure that your firearm is unloaded and pointed in a safe direction.

2. Installation:

- Align the XRT XRINGS with the Picatinny rail.
- Secure the rings using the provided Four (4) 832 x 1/2" CamcarTextron Torx drive screws.
- Tighten the left side of the cap first, followed by the right side, to prevent scope rotation.
- Ensure that the DoubleLug system fits securely into the crossslots of the rail.

3. Adjustment:

- After installation, check the alignment of the scope.
- Make any necessary adjustments to ensure proper eye relief and sight alignment.

4. Usage:

- Use the scope rings only with compatible scopes that fit the specified 30mm diameter.
- Always handle your firearm responsibly and in accordance with local laws and regulations.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding aluminum and metal products.
- Do not dispose of in regular household waste.
- Consider recycling the product if possible.

Contact Information for Further Support

For any questions or concerns regarding the XRT XRINGS Picatinny Scope Rings, please refer to the manufacturer's contact details provided with the product packaging.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk