

M17/M18 OPTIC MOUNTING PLATE WITH RSD - FORWARD CONTROLS DESIGN MILSPEC M17/M18 OPTIC MOUNTING PLATE, REAR SIGHT DOVETAIL

[Optics & Mounting](#) > [Electronic Sights](#) > [Mounting Hardware](#)

OPF-M17, ACRO, RSD is precision machined from 4140 steel, and QPQ coated. Aimpoint ACRO P1/P2 requires the plates to adhere to Aimpoint ACRO TDP with tight tolerances, OPF-M17, ACRO, RSD has proven to be the best choice among professional users. OPF-M17, ACRO, RSD is compatible with MIL issued M17/M18. It is a drop in adapter for superb Aimpoint ACRO sights. It is identical to the Tangodown SSM-03. OPF-M17, ACRO, RSD is compatible with P320 X-Five Legion, Legion Carry, and DP Cut. It is not compatible with P320 Pro Cut, P320 sub compact, AXG, and RX. OPF-M17-ACRO, RSD is shipped with two M4 0.7mm x 6mm (torque value: 20 to 25 in·lb), a T20 key, and a packet of VC-3. Proudly designed and made in the USA. ATTENTION: Steiner MPS users: MPS's recoil lug underneath the sight may vary in width and be slightly wider than that of the ACRO. Should this be the case, firmly push the MPS on the plate, or gently tap on the sight until the MPS fully seats. For the new M17/M18 and SIG P320 with the Delta Point Pro cut, Forward Controls Design is proud to offer OPF-M17, ACRO, RSD (rear sight dovetail).



Attributes

- Name: [FORWARD CONTROLS DESIGN MILSPEC M17/M18 OPTIC MOUNTING PLATE, REAR SIGHT DOVETAIL](#)
- Manufacturer: [FORWARD CONTROLS DESIGN](#)
- Product no.: 430103576
- Mfr. No.: OPF-M17, ACRO,
- Colour: Black
- Fits / Used For: Aimpoint ARCO
- Height: 0.24"
- Model: P320 M18,P320 M17
- Weapon type: Sig Sauer
- Weight: 1.3 lbs
- Delivery weight: 1.016kg
- Shipping height: 20mm
- Shipping width: 83mm
- Shipping length: 140mm
- UPC: 686162348015

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for M17/M18 Optic Mounting Plate with RSD Forward Controls Design
- About Us

Safety Instruction Guide for M17/M18 Optic Mounting Plate with RSD Forward Controls Design

Introduction

Thank you for choosing the M17/M18 Optic Mounting Plate with RSD from Forward Controls Design. This product is designed to enhance your shooting experience by providing a reliable mounting solution for Aimpoint ACRO sights. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Ensure safe use of this product by following all instructions outlined in this guide.
- Be aware of potential hazards associated with the installation and use of the optic mounting plate.
- If you are unfamiliar with firearm accessories, seek assistance from a qualified professional.
- Always handle firearms and accessories with care and respect.
- Keep the product out of reach of children and unauthorized users.
- Report any unsafe products or incidents to the appropriate authorities.
- Stay updated on recall notices and safety alerts through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Ensure that the M17/M18 Optic Mounting Plate is compatible with your firearm model (P320 M17, P320 M18).
- Inspect the product for any damage or defects before installation. Do not use if damaged.
- Follow all manufacturer guidelines regarding torque specifications during installation to avoid damaging the product or firearm.
- When installing the optic, ensure that the sight is securely seated to prevent movement during use.
- For users of Steiner MPS, ensure the recoil lug is properly seated on the plate to maintain stability.
- Avoid using the product if you are unsure of its installation or compatibility with your firearm.

Instructions for Installation and Usage

Installation Steps

1. **Preparation:** Gather all necessary tools, including two M4 0.7mm x 6mm screws, a T20 key, and a packet of VC3.
2. **Check Compatibility:** Verify that your firearm is compatible with the M17/M18 Optic Mounting Plate.
3. **Positioning:** Align the mounting plate with the dovetail of your firearm's rear sight. Ensure that it is correctly oriented.
4. **Secure the Plate:**
 - Insert the M4 screws into the designated holes of the mounting plate.
 - Use the T20 key to tighten the screws.
 - Apply a torque value between 20 to 25 in·lb to secure the plate. Do not overtighten.
5. **Install the Optic:** Place your Aimpoint ACRO sight onto the mounted plate. Ensure it is fully seated.
6. **Final Check:** Doublecheck all screws and the seating of the optic before using the firearm.

Usage Guidelines

- Always verify that your firearm is unloaded before installation or adjustment.
- Regularly inspect the mounting plate and optic for signs of wear or damage.
- Do not modify the product or use it in any way other than intended.
- Follow all local laws and regulations regarding the use of firearms and accessories.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- If the product is damaged or no longer usable, ensure it is disposed of safely to prevent any potential hazards.
- Recycling options may be available; check with your local waste management authority for guidance.

Contact Information for Further Support

For any inquiries regarding the M17/M18 Optic Mounting Plate with RSD, please refer to the manufacturer's contact information provided in the product packaging or on the official website.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk