

SIGHT PLUNGER SPRING, REAR - SMITH & WESSON SIGHT PLUNGER SPRING, REAR FOR S&W MODEL 41

[Handgun Parts](#) > [Sights](#) > [Sight Parts](#) > [Sight Springs](#)

FITS: 41, .22; 52 R2, .38 Spl; 4006, .40 S&W; 4506, .45 ACP; 5903, 9mm; 5904, 9mm; 5906, 9mm; M52-2, 38 SPL; 34, .22; 36, .38; 60-4, .38, .357; 63, .22; 631/631 LS, .32 Mag; 14, .38; 15-4, .38; 16, .32 Mag; 17-4, .22; 18-4, .22; 19, .357; 6

SIGHT PLUNGER SPRING, REAR



Attributes

- Name: [SMITH & WESSON SIGHT PLUNGER SPRING, REAR FOR S&W MODEL 41](#)
- Manufacturer: [SMITH & WESSON](#)
- Product no.: 940036390
- Mfr. No.: 036390000
- Model: 41
- Weapon type: Smith & Wesson
- Delivery weight: 0.005kg
- Shipping width: 83mm
- Shipping length: 146mm

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for SIGHT PLUNGER SPRING, REAR SMITH & WESSON SIGHT PLUNGER SPRING, REAR FOR S&W MODEL 41](#)
- [About Us](#)

Safety Instruction Guide for SIGHT PLUNGER SPRING, REAR SMITH & WESSON SIGHT PLUNGER SPRING, REAR FOR S&W MODEL 41

Introduction

Thank you for choosing the SIGHT PLUNGER SPRING, REAR for your Smith & Wesson Model 41. This guide provides essential safety instructions to ensure the safe use and handling of this product. Please read this manual thoroughly before installation and use.

General Safety Guidelines

- Always handle the SIGHT PLUNGER SPRING with care to avoid injury.
- Ensure that the product is compatible with your specific model (S&W Model 41).
- Store the product in a safe place, out of reach of children and pets.
- Regularly inspect the product for any signs of wear or damage before use.
- Follow all local laws and regulations regarding the use of firearms and firearm accessories.

Specific Safety Precautions for Use

- Do not use the SIGHT PLUNGER SPRING if it appears damaged or worn.
- Ensure that all tools and equipment used during installation are in good condition.
- Wear appropriate safety gear, such as safety glasses, when handling or installing the spring.
- Keep fingers and hands clear of any moving parts during installation.
- Do not exceed the manufacturer's specifications for installation and usage.

Instructions for Installation and Usage

1. Preparation

- Ensure that your firearm is unloaded and pointed in a safe direction.
- Gather necessary tools (e.g., screwdrivers, pliers) for installation.

2. Installation Steps

- Carefully remove the existing sight plunger spring from the firearm.
- Inspect the area for any debris or damage before installing the new spring.
- Align the new SIGHT PLUNGER SPRING with the designated slot in the firearm.
- Gently press the spring into place, ensuring it is seated correctly.
- Reassemble any components that were removed during the installation process.

3. Usage

- After installation, conduct a function test to ensure proper operation.
- Regularly check the spring for proper tension and alignment during use.

Disposal Instructions

- Dispose of the SIGHT PLUNGER SPRING in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Check with local authorities for specific disposal guidelines for firearm accessories.

Contact Information for Further Support

For any inquiries or concerns regarding the SIGHT PLUNGER SPRING, please refer to the EUbased contact point provided by your retailer or manufacturer. You can also check for safety updates and recall information on the EU's Safety Gate platform.

Thank you for adhering to these safety instructions. Your safety and the safety of others depend on the proper installation and use of this product.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk